



### 型式：CLシリーズ

ポンプ モデル	理論吐出量 ℓ/100RPM	最高差圧 MPa	コネクション		最高回転数 RPM	最高モーター KW
			スタンダード 外径 (mm)	ポート 内径 (mm)		
CL/0S/006/10	6.0	1.0	25	22	960	2.0
CL/0S/008/7	8.5	0.7	40	34	960	2.0
CL/1H/012/20	12.0	2.0	25	22	960	4.0
CL/1S/021/10	21.0	1.0	40	34	960	4.0
CL/1S/028/6	28.0	0.6	50	48	960	5.5
CL/1G/012/6	12.0	0.6	25	22	960	2.0
CL/1L/021/3.5	21.5	0.35	40	34	960	3.0
CL/1L/028/2	28.0	0.2	50	48	960	3.0
CL/2H/036/20	36.0	2.0	50	48	720	11.0
CL/2S/052/10	52.0	1.0	50	48	720	11.0
CL/2S/066/8	66.0	0.8	80	71	720	11.0
CL/2G/036/10	36.0	1.0	50	48	720	5.5
CL/2L/052/5.5	52.0	0.55	50	48	720	5.5
CL/2L/066/3.5	66.0	0.35	80	71	720	4.0
CL/3H/078/20	78.0	2.0	80	71	720	22.0
CL/3S/107/10	107.0	1.0	80	71	720	18.5
CL/3S/156/7	156.0	0.7	100	98	720	22.0
CL/3G/078/10	78.0	1.0	80	71	720	11.0
CL/3L/107/5.5	107.0	0.55	80	71	720	11.0
CL/3L/156/3.5	156.0	0.35	100	98	720	11.0
CL/4H/182/30	182.0	3.0	80	71	650	75.0
CL/4S/285/15	285.0	1.5	100	98	650	75.0
CL/4S/385/9	385.0	0.9	125	126	650	75.0
CL/4G/182/20	182.0	2.0	80	71	650	55.0
CL/4L/285/10	285.0	1.0	100	98	650	55.0
CL/4L/385/6	385.0	0.6	125	126	650	55.0
CL/5H/344/30	344.0	3.0	100	98	600	110.0
CL/5S/508/15	508.0	1.5	125	126	600	110.0
CL/5S/620/10	620.0	1.0	150	155	600	110.0
CL/5G/344/20	344.0	2.0	100	98	600	90.0
CL/5L/508/10	508.0	1.0	125	126	600	90.0
CL/5L/620/7	620.0	0.7	150	155	600	90.0